

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch disconnecter, size 00 to 3 – SV 9343.000

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch disconnector, size 00 to 3 – SV 9343.000

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Polyamide (PA 6)
Fire protection corresponding to UL 94-V0
Contact tracks: Electrolytic copper, silver-plated

Color: Chassis: RAL 7035
Cover: RAL 7035/7001

Basis of test: IEC 60 947-3
IEC 60 269-2 (fuse inserts)

Note: The technical data may vary in the case of UR applications. UR applications only in conjunction with "Special Purpose Fuses".

Product features

Version: Size: 00

Suitable for busbars: with cross-section height: 5 mm (0.2 ")
with cross-section height: 10 mm (0.39 ")

Number of poles: 3-pole

For bar systems with center-to-center spacing: 60 mm

Dimensions: Height: 194 mm (7.6 ")
Width: 106 mm (4.2 ")

Type of connection Box terminal

(electrical):

Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Height: 13 mm (0.51 ") Width: 13 mm (0.51 ")
Connection for round conductor cross-sections:	4 mm ² - 95 mm ²
Rated operating current max.:	160 A
Cable outlet:	Top/bottom
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.94 kg (2.1 lb.)
EAN:	4028177540255
Customs tariff number:	85369095
ETIM 6.0:	EC001040
ETIM 5.0:	EC001040
eCl@ss 8.0/8.1:	27371401
eCl@ss 7.0/7.1:	27371401
eCl@ss 6.0/6.1:	27371401
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV NH fuse-switch disconnecter, size 00, 160 A, 690 V, 3-pole, box terminal
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity