

Rittal – The System.

Faster – better – everywhere.

PK Polycarbonate Housings without knockouts – PK 9514.100

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PK Polycarbonate Housings without knockouts – PK 9514.100

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Applications: Ambient temperature range: -35°C...+80°C
The specified temperatures can be limited by the installed equipment

Material: Housing: Fiber-glass reinforced polycarbonate
Cover transparent: Polycarbonate, all-round foamed-in PU seal
Cover screws: Polyamide
Insulating bungs: Polythene

Color: RAL 7035

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with cover
Cover screws
Insulating bungs for wall mounting screws

Base material: Polycarbonate

Product features

Dimensions: Height: 110 mm (4.3 ")
Width: 180 mm (7.1 ")
Depth: 90 mm (3.5 ")

Cover: transparent

Ambient temperature range:	-35°C...+80°C
Packaging unit:	2 pc(s).
Weight/packaging unit:	0.86 kg (1.9 lb.)
EAN:	4028177139510
Customs tariff number:	94037000
ETIM 6.0:	EC000261
ETIM 5.0:	EC002600
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	PK Polycarbonate enclosure, WHD: 180x110x90 mm, fibreglass-reinforced polycarbonate, without knockouts, with transparent cover
Approvals	
Approvals:	Bureau Veritas C-UL UL
Declarations:	Declaration of conformity