# T&B Conduit Fittings

## Rigid and Intermediate Metal Conduit Fittings




***Eliminate conduit threading with these set screw fittings. Captive hex head screws tighten down onto conduit for positive holding strength and ground. The fittings are furnished with insulated throats reducing wire pulling effort by as much as 50%. Approved concrete-tight.***

### Insulated Set-Screw Fitting

| Cat. No. | Conduit Size | Dimensions (in.) A | Dimensions (in.) B |
|---|---|---|---|
| **8125** | 1/2" | 1-3/8 | 13/32 |
| **8225** | 3/4" | 1-1/2 | 7/16 |
| **8325** | 1" | 1-13/16 | 35/65 |
| **8425** | 1-1/4" | 2 | 5/8 |
| **8525-TB** | 1-1/2" | 2-5/16 | 5/8 |
| **8625** | 2" | 2-7/16 | 11/16 |
| **8725-TB** | 2-1/2" | 3-3/8 | 1 |
| **8825** | 3" | 3-7/16 | 1 |
| **8855** | 3-1/2 | 3-7/8 | 1-1/16 |
| **8975** | 4" | 4-3/16 | 1-1/8 |

*Sizes 1/2"-2" made of steel. Sizes 2-1/2"-4" are malleable iron.*
*For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.*




***Eliminate the need for threading conduit ends when joining rigid conduit with these set screw couplings. Captive hex head screws provide positive holding strength and ground continuity.***
***Approved concrete-tight.***

### Set Screw Coupling

| Cat. No. | Conduit Size | Dimensions (in.) A |
|---|---|---|
| **8124** | 1/2" | 2-1/2 |
| **8224-TB** | 3/4" | 2-11/16 |
| **8324-TB** | 1" | 2-27/32 |
| **8424** | 1-1/4" | 3 |
| **8524** | 1-1/2" | 3-3/8 |
| **8624** | 2" | 3-5/8 |
| **8724-TB** | 2-1/2" | 3-7/8 |
| **8824-TB** | 3" | 4-1/4 |
| **8854** | 3-1/2 | 4-15/16 |
| **8974** | 4" | 5-3/8 |

*Sizes 1/2"-2" made of steel; sizes 2-1/2"-4" are malleable iron.*
*For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.*