Rittal – The System.

Faster – better – everywhere.

CMC III Power Packs – DK 7030.060

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

CMC III Power Packs – DK 7030.060

created: 24.05.2018 build on www.rittal.com/us-en

Product description

Description:	For CMC III Processing Unit, CMC III Processing Unit Compact, Fan Control System.
Applications:	CMC III Processing Unit CMC III Processing Unit Compact CMC III CAN bus unit CMC III CAN bus DRC CMC III Door Control System
Material:	Plastic
Color:	Front: RAL 9005 Housing: RAL 7035
Supply includes:	Power pack Instructions Top-hat rail assembly kit Assembly components

Product features

Suitable for CMC components:	CMC III Processing Unit CMC III Processing Unit Compact CMC III CAN Bus Interface for Two CMC II Unit Components
Dimensions:	Height: 40 mm (1.6 ″) Width: 138 mm (5.4 ″) Depth: 132 mm (5.2 ″)
Rated operating voltage:	100 V - 240 V, 50 Hz/60 Hz

Installation dimensions:	Installation depth: 120 mm (4.7 ″) Build depth: 12 mm (0.47 ″)
Operating temperature:	Operation (environment): +0°C...+40°C
Ambient humidity (non-condensing):	Operation (environment): 5 % - 95 %
Power pack:	Output voltage: 24 V DC
Output current (max.):	2.5 A
Connections:	Input: Non-heating apparatus connector C14
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.65 kg (1.4 lb.)
EAN:	4028177659384
Customs tariff number:	85043121
ETIM 6.0:	EC002627
ETIM 5.0:	EC002627
eCl@ss 8.0/8.1:	27189253
eCl@ss 7.0/7.1:	27189253
eCl@ss 6.0/6.1:	27189253
eCl@ss 5.1/5.1.4:	27189253
Product description (long):	DK CMC III Power pack, For power supply of the CMC III Processing Units, Input: C14 100-230 V, 50/60 Hz, Output: 24 V DC, 2 A

Approvals

Approvals:	UL
Certificates:	EAC
Declarations:	Declaration of conformity