



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Ferrule style high speed fuse links

**FWP-80A22F**

**UPC:**051712370875

### Dimensions:

- **Height:** 50 MM
- **Length:** 58 MM
- **Width:** 23 MM

**Weight:**.042 KG

### Warranties:

- Not Applicable

### Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 80A
- **Voltage Rating:** 700 Vac, 700 Vdc (UL)
- **Interrupt Rating:** 200 KAIC, 50 KAIC at 300 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I2T):** 550
- **Clearing (I2T):** Clearing at Rated voltage: 6600
- **Minimum Melting:** 600 I2t (A2 Sec)
- **Diameter:** 22 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** Class aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 13.5W
- **Mounting:** Fuse holder and blocks
- **Quantity:** 10



- **Fuse Size:** 22 x 58 mm

**Supporting documents:**

- [80AMP 700V ac 22 X 58MM FERRULE](#)

**Certifications:**

- CSA Certified
- UL Recognized

**Product compliance:**

- CE Marked
- RoHS Compliant