



TMHG92

by Burndy Catalog ID: TMHG92

Prop65

Stainless Steel Hardware Kit For I-Beam Connector, 1/2" Screw, 0.92" Max. Terminal Pad Thickness.

GROUNDLINK connectors are made of high-conductivity wrought copper and come pre-filled with PENETROX E compound and strip sealed. Order terminal mounting hardware separately.

Product Details

General

Application	An irreversible compression ground connection which allows attachment to a structural steel standard (angled) or wide flange (para llel) beam.
Connector Type	Hardware
Item Type	3B
Material	Stainless Steel
Sub Brand	INSULUG
Туре	Compression Ground Connector
UPC	781810035061
UPC 12 Digit	7818100350611

Dimensions

	1/0 17			
Dimension - Thread Size	1/2 - 13			
	, -			

Certifications and Compliance

Cartification CCA Approved	Nie
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	• UL468A-468B • IEEE 837
Standards - Industry Standards Met	UL468A-468BIEEE 837
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)