



## PLUGTAIL® COMMERCIAL SPECIFICATION GRADE 20A USB CHARGING RECEPTACLES, BROWN

PTTR20ACUSB | [Pass & Seymour](#)

### FEATURES & BENEFITS

PlugTail® Commercial Specification Grade USB Charging Receptacles provide the convenience of mobile charging – without the need for a bulky AC adapter. This device is a perfect match for the constant needs of today’s mobile environment and is rugged enough to withstand hard-use commercial applications. It comes equipped with two UL Fed Spec AC receptacles and two USB charging ports for mobile devices – one Type-A port and one Type-C port for newer products. An efficient, 15.5W power supply provides ample power needed for charging mobile phones and tablets. The PlugTail termination provides a more productive, secure, and safer installation and allows you to connect with the future of wiring device innovations.

For detailed PlugTail® information, visit our [PlugTail Headquarters](#).

- **AC receptacles are tamper resistant as standard** – patented shutter system prevents improper insertion of foreign objects
- **Efficient, 15.5W power supply** for fast charging of mobile phones and tablets
- **Triple-wipe, brass line contacts** for 20A commercial applications
- Multiple color options available
- **Zinc-plated steel** for corrosion resistance
- **5Vdc Type-C USB port** to charge USB Type-C compatible mobile devices
- **PlugTail termination** allows for more productive, finger-safe installation and added future flexibility
- **Stainless steel auto-ground clips** assure positive ground
- Available in 15 & 20A, Specification Grade and Hospital Grade configurations
- For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

### SPECIFICATIONS

#### GENERAL INFO

Color: Brown

Available Colors: Ivory, White, Light Almond, Black, Gray

Type: Duplex PlugTail Receptacles

Special Features: Type-A and Type-C USB port

#### LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

CSA Listing Info: C22.2 No. 42, C22.2 No. 228  
CSA Standard: Yes  
cULus: Yes  
Federal Spec: Yes  
UL Listing No: Complies with test requirements UL 498, UL 1312  
UL Standard: Yes

#### **DIMENSIONS**

Depth (US): 1.45"  
Height (US): 3.281"  
Width (US): 0.69"

#### **TECHNICAL INFORMATION**

Amps: 20A  
Material: Thermoplastic  
NEMA Configuration Number: 5-20R  
NEMA Rating: Yes  
Operating Temperature (Celsius): Maximum continuous +60°C, minimum -40°C without impact  
Volts: 125V

#### **BUY AMERICAN ACT COMPLIANCE**

Country Of Origin: MEXICO

