

Non - Watertight Connectors

Type 800F & Type 900F

2-Screw double clamp

Use:

For securing SEU and other oval (flat) non-metallic cables to boxes and enclosures in dry locations.

Features:

- Open throat type
- Male hub threads - NPS
- Furnished with locknuts

Material/Finish:

Malleable Iron, Zinc Electroplated

Third Party Certification:



UL Listed: E-11856

UL Listed for NM and SE Cables.




CSA Certified: 11584

Applicable Third Party Standards:


UL Standard: 514B

CSA Standard: C22.2 No. 18

Fed. Spec: W-F-406E



Type 806F



Type 906F

Trade Size (inches)	Catalog Number	SEU Cable Range (Braid Neoprene and PVC Jacketed)	Clamp Opening Range			Dimensions in Inches		
			Min.	Max.	Width	Body Length	Hub Thread Length	Turning Dia.
3/4	806F	3#10 to 3#6	.33	.82	.82	1 1/16	7/16	1 3/16
1	906F	3#10 to 3#2	.30	1.06	1.06	1 1/16	9/16	2 1/16
1 1/4	907F	3#3 to 3#1/0	.50	1.35	1.35	1 3/16	9/16	2 1/16
1 1/2	908F	3#1/0 to 3#3/0	.59	1.11	1.56	7/8	5/8	2 3/4
2	909F	3#2/0 to 3#4/0	.77	1.14	1.78	1 5/16	3/4	3 3/8

Type 806 & Type 900

2-Screw double clamp

Use:

For securing SEU and other round non-metallic cables to boxes and enclosures in dry locations.

Features:

- Open throat type
- Available with insulated throat.
- Male hub threads - NPS
- Furnished with locknuts

Material/Finish:

Malleable Iron/Zinc Electroplated

Third Party Certification:



806, 906Z, 907: UL Listed: E-11856


UL Listed for SE Cables.

806, 906Z, 908, 909:


UL Listed: E-11858

UL Listed for NM and SE cables.

CSA Certified: 11584 (NM cable)



Type 806



Type 909

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Clamp Opening Range			Dimensions in Inches		
			Min.	Max.	Body Width	Thread Length	Hub Turning Length	Dia.
3/4	806	806T	.37	.84	.84	1 1/16	7/16	1 3/16
1	906Z	906T	.42	1.05	1.05	1 1/16	9/16	2 1/16
1 1/4	907*	907T*	.73	1.34	1.34	1 3/16	9/16	2 1/16
1 1/2	908*	908T*	.91	1.45	1.55	7/8	5/8	2 3/4
2	909*	909T*	1.39	2.03	2.03	1 1/16	3/4	3 3/8

*Not CSA Certified.

Applicable Third Party Standards:

UL Standard: 514B

CSA Standard C22.2 No. 18

Fed. Spec: W-F-406E