



9 KVA CL1 DIV2 HAZ LOC XFMR 3PH 480V DELTA-208Y/120V 115C

Z48G28T09A

UPC:786680006258

Dimensions:

Height: 12.06 INLength: 10.01 INWidth: 16.93 IN

Weight:213 LB Notes:Model A

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

 Type: Class 1 Division 2 Groups C and D, Hazardous Location Transformer

• Design: EPTZ

Coil Material: Aluminum windings

• Enclosure: NEMA 3R

• Frame: 103H

• Frequency Rating: 60 Hz

• Phase: Three-phase

• Primary Voltage: 480V

• Secondary Voltage: 208Y/120V

• Tap Size: 2 at -5% FCBN

• Temperature Rating: 115°C

• Volt Ampere Rating: 9 KVA

• Weathershield: Indoor-Outdoor

• Wiring Connection: 70A

Supporting documents:

• Eatons Volume 2-Commercial Distribution



• Eaton Specification Sheet - Z48G28T09A

Certifications:

• UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.