




**CATALOG NUMBER:** See table below  
**DESCRIPTION:** SJTW replacement power supply cords  
**APPROVALS:** UL / CUL Listed

### CONSTRUCTION PARAMETERS:

Conductors: 16/3  
 Conductor stranding: 26/30 Bare Copper  
 Conductor O.D. (nom): 0.059in  
 Insulated conductor O.D. (nom): 0.120 in  
 Insulation material: PVC  
 Insulation colors: Black White Green  
 Overall cable O.D. (nom): 0.330 in  
 Jacket material: PVC, black



*Note: Plug style may vary*

Attachment plug configuration: NEMA 5-15P  
 Plug material: PVC, black  
 Open end configuration: 2.5" ROJ, 0.5" conductor strip & retain

### ELECTRICAL PROPERTIES:

Cable temperature rating: -40 to +60 °C  
 Nominal operating voltage: 125 VAC  
 Maximum operating current: 13 A

### CATALOG NUMBERS:

Catalog number	Length	Case qty	UPC
97038808	3 ft	25	0 29892 09703 5
97068808	6 ft	25	0 29892 09706 6
97098808	9 ft	25	0 29892 09709 7

*This product complies with European Directive 2011/65/EU (RoHS-2,*

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company LLC.