




*Commercial, Industrial
and Residential Electrical Products*

4 In. Square Box, 2-1/8 In. Deep, Welded, Ten 1/2 In. KO's and Six TKO's, Raised Ground, 8 In. #12 Solid Copper Pigtail, UBS, HM Bracket

Catalog #:
232M



FEATURE BENEFIT

Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices. Built in bracket or supports speeds installation.

PRODUCT FEATURES

- UBS integrated support provides bracing on back of box for wall cavities between 2-1/2 In - 6 In. thickness, HM Bracket
- Combination screw heads allow quick installation
- Welded construction
- Ten 1/2 In. knockouts and Six TKO knockouts
- 30.3 Cu. In. capacity
- Raised ground, 8 In. #12 Solid Copper pigtail
- Acceptable in 2-hour fire rated walls

APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

CERTIFICATIONS



PRODUCT SPECIFICATIONS

UPC Number:	050169500040
Ea Length/Depth (in.):	2.676
Ea Width (in.):	5.86
Ea Height (in.):	4.03
Wt. Ea. (Lbs.):	1.03
Package Type:	Loose
Product UPC-A Labeled:	No

PACKAGING

Case I2of5:	50050169500045
Standard Carton Qty:	25
Min Order Qty:	25



All RACO single-gang, two-gang, 4 In. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com

600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

Revision 1, March 2020



**COMMERCIAL
CONSTRUCTION**
A Division of Hubbell Incorporated (Delaware)

RACO
3902 W. Sample St.
South Bend, IN 46619
574-234-7151
www.hubbell.com/raco/en

