

# Rittal – The System.

Faster – better – everywhere.

## Enclosure Heaters without fan – SK 3105.340

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Enclosure Heaters without fan – SK 3105.340

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Supply includes:** PTC heater  
Quick-connection terminal  
Fasteners

**Note:** For precise temperature control inside the enclosure, we recommend using the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, hygostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.

**Note on Model No.:** Special voltages available on request. We reserve the right to make technical modifications.

## Product features

**Continuous thermal output at 10°C:** 49 W - 50 W

**Rated operating voltage:** 110 V - 240 V, 1~, 50 Hz/60 Hz

**Dimensions:** Height: 155 mm (6.1 ")  
Width: 64 mm (2.5 ")  
Depth: 56 mm (2.2 ")

**Miniature circuit-breaker/fuse:** 4 A

**Packaging unit:** 1 pc(s).

**Weight/packaging unit:** 0.4 kg (0.9 lb.)

<b>EAN:</b>	4028177638648
<b>Customs tariff number:</b>	85162999
<b>ETIM 6.0:</b>	EC000737
<b>ETIM 5.0:</b>	EC000737
<b>eCl@ss 8.0/8.1:</b>	27180710
<b>eCl@ss 7.0/7.1:</b>	27180710
<b>eCl@ss 6.0/6.1:</b>	27180710
<b>eCl@ss 5.1/5.1.4:</b>	27180710
<b>Product description (long):</b>	SK enclosure heater, without fan, 49-50 W, 110-240 V, 1~, 50/60 Hz, WHD: 64 x 155 x 56 mm

## Approvals

<b>Approvals:</b>	Approval overview CSA UR + C-UR VDE
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity