

# Metal Raceway

## HBL500 and HBL750 Series

Fittings



	HBL500 and HBL750 Series		HBL500 and HBL750 Series			
	Description	Color	Description	Color		
End Fittings	<b>Entrance Connector</b> One ¼ in. KO for panel or conduit connection. One ¼ in. chase nipple and locknut furnished.	Ivory White	<b>HBL5786AIV</b> <b>HBL5786AW</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	<b>Adjustable Offset Connector</b> Two ½ in. KOs for panel or conduit connection. Eliminates offsetting raceway when connecting to surface type panel boxes. One ½ in. chase nipple and locknut furnished.	Ivory White	<b>HBL5786IV</b> <b>HBL5786W</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)
	<b>Elbow Box Connector</b> For connecting raceway at right angles to conduit boxes, panel boxes, etc. having ½ in. nipple for trade size conduit.	Ivory	<b>HBL5783IV</b> A: 2.13" (54.05) B: 1.24" (31.50)	<b>Elbow Conduit Connector</b> For connecting raceway at right angles to ½ in. trade size conduit or armored cable connectors.	Ivory	<b>HBL5784IV</b> A: 2.13" (54.05) B: 1.24" (31.50)
	<b>Combination Connector</b> For connecting raceway without offsetting to any 3.25 in. (83.00) or 4 in. (102.00) outlet box mounted on the surface with a KO for ½ in. trade size conduit. Spring steel bushing eliminates need for conduit nipple and locknut.	Ivory White	<b>HBL5785AIV</b> <b>HBL5785AW</b> A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	<b>Corner Box</b> For connecting HBL500 or HBL750 Raceway from ceiling or corner. Each leg of base has ½ in. trade size KO.	Ivory White	<b>HBL5719IV</b> <b>HBL5719W</b> A: 2.50" (63.50) B: 2.50" (63.50) C: 2.40" (60.96)

	HBL500 Series		HBL750 Series		HBL500 and HBL750 Series		
	Description	Color	Description	Color	Description	Color	
Fittings	<b>Mounting Strap</b> (one- or two-hole) For mounting HBL500 or HBL750 Raceway to surface. Convert to one-hole by breaking off at score.	Ivory White	<b>HBL504IV</b> <b>HBL504W</b> A: .58" (14.73) B: .50" (12.70)	<b>HBL704IV</b> <b>HBL704W</b> A: .90" (22.86) B: .50" (12.70)	<b>Support Clip</b> For supporting lengths of HBL500 or HBL750 Raceway.	Ivory White	<b>HBL5703IV</b> <b>HBL5703W</b> A: 2.51" (63.75)
	<b>Connection Cover</b> To cover potential openings where two lengths of HBL500 or HBL750 Raceway come together.	Ivory White	<b>HBL506IV</b> <b>HBL506W</b> A: .60" (15.24) B: .80" (20.31)	<b>HBL706IV</b> <b>HBL706W</b> A: .91" (23.10) B: .80" (20.31)	<b>Flexible Section</b> For getting around offsets, side bends, twisted turns or curved surfaces.	Ivory	<b>HBL5700FIV</b> A: 18.00" (457.20)
	<b>Transition Fitting</b> For transitioning from either Wiremold® V500 to Hubbell HBL500 Raceway or Wiremold® V700 to Hubbell HBL750 Raceway.	Ivory	<b>HBL500TFIV</b> A: .65" (16.51) B: .89" (22.61) C: 2.15" (54.61)	<b>HBL750TFIV</b> A: .98" (24.89) B: .89" (22.61) C: 2.15" (54.61)			
	<b>Bushing</b> Protect wires from potential abrasion. Fits into end of HBL500 or HBL750 Raceway.	Steel*	<b>HBL502B</b> A: .35" (8.83) B: .70" (17.68)	<b>HBL702B</b> A: .60" (15.24) B: .70" (17.68)			

Note: \* Zinc Plated Steel.

Wiremold® is a registered trademark of the Wiremold Company.

