



QPX2C2CY

by Burndy
Catalog ID: QPX2C2CY

Prop 65 Notice

Cast Copper Alloy Versitap, Tin Plated.

Features: High Copper Alloy Cast Connector, Tin-Plated For Use With Copper Or Aluminum Cable, Makes Parallel, Tap, Tee, Cross Or End-To-End Connections, Edges Rounded For Easy Taping, PENETROX Joint Compound Recommended, Number Of Bolts: 2, Conductor Type: Run: Commercial Stranded Aluminum, Commercial Stranded Copper, Tap: Commercial Stranded Aluminum, Commercial Stranded Copper, Installation Torque: 150 IN-LB, Length: 1-1/2 IN, Height: 1-5/8 IN, Width: 1-5/8 IN

Product Details

General

Application	For Use With Copper Or Aluminum Cable
Installation Torque Recommended in-lb	150 LBS/in
Material	Copper
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	Y
Plating Type	Tin
Sub Brand	VERSITAP
Temperature Rating	194
Trade Name	VERSITAP™
Type	QPX-Y, Universal
UPC	781810341803
UPC 12 Digit	7818103418033

Dimensions

Dimension - B Length fraction	1-1/2 in
Dimension - B Length inch	1.52 in
Dimension - Height fraction	1-5/8 in
Dimension - Height inch	1.59
Dimension - L Length Overall mm	38 mm
Dimension - Length Overall inch	1.50 in
Dimension - Width fraction	1-5/8 in
Dimension - Width inch	1.61
Dimension - Width mm	41 mm

Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

Conductor Related

Conductor - AL Str Run	6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Run Range	6 AWG-2 AWG
Conductor - AL Str Tap	6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Tap Range	6 AWG-2 AWG
Conductor - Copper Str Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Run Range	6 AWG-2 AWG
Conductor - Copper Str Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Tap Range	6 AWG-2 AWG
Conductor Type	• AL C Str-Run • CU C Str-Run • AL C Str-Tap • CU C Str-Tap

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	24
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)