

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable – DK 7712.135

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part with punched rails and profile rails, depth-variable – DK 7712.135

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: with punched rails and profile rails, depth-variable

Description: Wall-mounted enclosure with hinged door provides optimum accessibility.

Material: Wall and hinged part: Carbon steel, 1.5 mm
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Color: Wall and hinged part: RAL 7035
Viewing door: RAL 7035/7015 (slate gray)

**Protection category
IP to IEC 60 529:** IP 55

Supply includes: Wall section closed at top and bottom with flange (gland) plate, two vertical mounting rails and horizontal C-profile rails for cable clamping.
Hinged part with 25 mm pitch pattern in the front and rear frame, two 482.6 mm (19") profile angles at the front, fully depth adjustable
4 wall mounting brackets 10 mm
Designer viewing door
1 enclosure key double bit no. 5
Mini-comfort handle
Security lock 3524 E

Base material: Carbon steel

Product features

Dimensions:	Height: 612 mm (24 ") Height units: 12 U (12 U) Width: 600 mm (24 ") Depth: 473 mm (19 ")
Depth hinged part:	316 mm (12 ")
Installation depth:	420 mm (17 ")
Clearances:	Clearance height: 549 mm (22 ") Clearance width: 502 mm (20 ")
Wall section:	Depth: 135 mm (5.3 ")
Load capacity:	Hinged part, static (max.): 600 N (600 N)
Packaging unit:	1 pc(s).
Weight/packaging unit:	36 kg (79.4 lb.)
EAN:	4028177324190
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27142408
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	DK Wall-mounted enclosures, 3-part, WHD: 600x612x473 mm, 12 U, With punched rails, and mounting angles, depth-variable

Approvals

Approvals:	UL + C-UL
Certificates:	Protection category