



**Commercial, Industrial  
and Residential Electrical Products**

## 4 In. Square Box, Welded, 2-1/8 In. Deep, Ten 1/2 In. KO's and Six TKO's, Raised Ground, 8 In. #12 Solid Copper Pigtail, UBS, HM Bracket

Catalog #:  
232H



### FEATURE BENEFIT

Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices. Built in bracket or supports speeds installation.

### PRODUCT FEATURES

- UBS integrated support provides bracing on back of box for wall cavities between 2-1/2 In - 6 In. thickness, H/M bracket
- Combination screw heads allow quick installation
- Welded construction
- Ten 1/2 In. knockouts and Six TKO knockouts
- UL Listed
- 30.3 cu. in. capacity
- Raised ground, 8 In. #12 solid copper pigtail
- Acceptable in 2-hour fire rated walls

### APPLICATIONS

Designed to enclose electrical wiring, switches, receptacles or lighting fixtures. Constructed from 1/16 In. pre-galvanized steel. 8-32 cover mounting screws assembled. Suitable for use without a bonding jumper in circuits up to 600V.

### CERTIFICATIONS



### PRODUCT SPECIFICATIONS

UPC Number:	050169500033
Ea Length/Depth (in.):	2.676
Ea Width (in.):	4.91
Ea Height (in.):	4.03
Wt. Ea. (Lbs.):	1.00
Package Type:	Loose
Product UPC-A Labeled:	No



All RACO single-gang, two-gang, 4 In. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at [www.ul.com](http://www.ul.com)

### PACKAGING

Case 12of5:	50050169500038
Standard Carton Qty:	25
Min Order Qty:	25

**600V** Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

Revision 1, March 2020



**COMMERCIAL  
CONSTRUCTION**  
A Division of Hubbell Incorporated (Delaware)

RACO  
3902 W. Sample St.  
South Bend, IN 46619  
574-234-7151  
[www.hubbell.com/raco/en](http://www.hubbell.com/raco/en)

