

Non-NEMA Twist-Lock® Devices  
10A, 250V/15A, 125V, 3 Pole, 3 Wire  
Non-Grounding  
Insulgrip® Connector

# HUBBELL

## Features

- Individually molded face for each blade configuration keeps debris out of plug interior
- Ribbed nylon housing is impact and chemical resistant
- Roomy wiring chamber provides ample space for wiring

## Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Black phenolic.	.296"-.625" (7.5-15.9)	783585237626	HBL7555



## Specifications

Housing	Phenolic
Contacts	Copper alloy
Terminal Screws	#5-40 Brass
Clamp Plate	Zinc plated steel
Cord Clamps/Screws	Zinc plated steel
Assembly Screws	Nickel plated brass

## Performance

### Electrical

Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

### Mechanical

Terminal Accommodation	#18 AWG - #10 AWG stranded copper wire only.
------------------------	--

Terminal Identification	Terminals identified in accordance with UL 498
-------------------------	--

### Environmental

Flammability	HB or better per UL94/CSA 22.2 No.0.17
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)

## Accessories

Plug	HBL7567C
Stainless Steel Flanged Inlet	HBL7556

## Resources

eCatalog
----------

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

