



BIT600FX

by Burndy
Catalog ID: BIT600FX

Prop 65 Notice

Insulated tap offset ports flex conductor rated, Wire size: #4-600 , Color: Green, Amp Rating : 420.

Features: Clear Plastisol covered AL6061-T6 aluminum body, Saves time, lowers installation costs, eliminates taping, Oxide inhibitor pre-installed, Inhibits moisture and contaminants from entering the contact area

Product Details

General

Application	Clear Insulated Multiple Tap Connectors
Color Code	Green
Hex Key	3/8 in
Insulation	Y
Insulation Type	Plastisol
Material	Aluminum
Number Of Ports	2
Plated	Y
Plating Type	Tin Plated
Sub Brand	UNITAP
Temperature Rating	135°C
Trade Name	UNITAP™
Type	BIT, UNITAP
UPC	621945440043
UPC 12 Digit	6219454400433

Dimensions

Dimension - Height inch	2.75 in
Dimension - L Length Overall mm	69.85 mm
Dimension - Length Overall inch	2.75 in
Dimension - Width inch	2.38 in
Dimension - Width mm	60.45 mm

Electrical Ratings

Operating Voltage	600 V
-------------------	-------

Conductor Related

Conductor - AL Str Size Range	4 str.-600 kcmil
Conductor - Copper DLO Size Range	4 str.-373 kcmil
Conductor - Copper Flex G Size Range	4 str.-373 kcmil
Conductor - Copper Flex H Size Range	4 str.-373 kcmil

Conductor - Copper Flex I Size Range	4 str.-373 kcmil
Conductor - Copper Flex K Size Range	4 str.-373 kcmil
Conductor - Copper Str Size Range	4 str.-600 kcmil
Conductor Type	• AL C Str-Size • CU C Str-Size • CU C Flex-Size

Certifications and Compliance

Certification - CSA Approved	No
Industry Standard(s)	UL468A-468B
Standards - Industry Standards Met	UL468A-468B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)