

BALDOR® • RELIANCE

Product Information Packet

FDL3731M

5HP,1740RPM,1PH,60HZ,215,3730LC,TEFC,F1

Part Detail									
Revision:	-	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3730LC	Elec. Spec:	37WGT880	CD Diagram:			
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	37K226	Layout:			
Frame:	215	Mounting:	F1	Poles:	04	Created Date:	08-23-2010		
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	09-02-2010		
Leads:	2#12 A PH,3#14 B&L	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1280L									
CAT.NO.	FDL3731M								
SPEC.	37K226T880								
HP	5								
VOLTS	230								
AMP	20.5								
RPM	1740								
FRAME	215	HZ			60	PH	1		
SER.F.	1.00	CODE			J	DES	L	CL	F
NEMA-NOM-EFF	84	PF			93				
RATING	40C AMB-CONT								
CC				USABLE AT 208V					
DE	6307	ODE			6206				
ENCL	TEFC	SN							

Parts List		
Part Number	Description	Quantity
SA201945	SA 37K226T880	1.000 EA
RA189237	RA 37K226T880	1.000 EA
OC3030F11SP	CYL OIL CAP 30MFD/370V	2.000 EA
TPLED1027SP	THERMAL 1PH 1.5 MAN REF LED989 TDR #5817	1.000 EA
EC1189C06SP	ELEC CAP, 189-227 MFD, 250V, 2.06D X 4.	3.000 EA
37FN3002A01SP	EXFN, PLASTIC, 9.00 OD, 1.155 ID	1.000 EA
TP5059	GENERIC THERMAL KIT	1.000 EA
HW3200A01	3/8-16X3/4 I-BLT WELDED F/S	1.000 EA
37CB3804A04	CAPAC BOX MACH	1.000 EA
37GS3015	GASKET, CAPAC BOX	1.000 EA
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	4.000 EA
37CB4509	CAPAC BOX LID, STAMPED	1.000 EA
37GS3016	GASKET, CAPAC BOX LID	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	6.000 EA
HA6003A47	CAPAC CLAMP	1.000 EA
HA6003A45	CAPAC CLAMP - CLIP (WHITE ZINC PLATED)	2.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	4.000 EA
HA2001A09	SPACER, .218 ID X .937 LG	2.000 EA
RM1015	BOOT FOR MANUAL THERMALS	1.000 EA
51XN1032A28	10-32 X 1 3/4 HX WS SL SR	2.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	2.000 EA
HW1000A10	#10 FLAT WASHER (SAE)	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW3001B01	003SS CUP WASHER, FOR #8 SCREW	1.000 EA

Parts List (continued)

Part Number	Description	Quantity
37EP3101A01SP	FR ENDPLATE,TEFC, 37 L&M, W/GREASER	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
13XT0832A07	8-32X7/16 TYP 23 PAN HD SLT DX	2.000 EA
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 EA
37EP3100A01SP	STD PU ENDPLATE, ENCL,37 "T"-307 BRG, W/	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 EA
07FH4007A06	IEC FH W/GRS, NOT @6, 3 F/C HOL & NOT FO	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
51XB1214A20	12-14X1.25 HXWSSLD SERTYB	1.000 EA
HA1005A07SP	SLINGER, OD 2.25, ID 1.344, 307 BRG	1.000 EA
HW2501E18	KEY, 1/4 SQ X 2.000	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
LB1115	LABEL,LIFTING DEVICE	1.000 EA
LB1087	LABEL,MANUAL RESET (ROLL LABEL)	1.000 EA
NS2539	INSULATOR FOR 37 FRAMESWITCH (MH1011A10)	1.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB
MG1025C02	PAINT, 787.105 LITE TAN EPOXY (USE W/MG1	0.028 GA
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
HA3104A17	5/16-18X13.250 T-BLT/OHIO	4.000 EA
SP5172A03	37 TYPE L TORQ STAT SWITCH LEAD ASSEMBLY	1.000 EA
LB1119	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA

Parts List (continued)

Part Number	Description	Quantity
LC0002	CONNECTION LABEL	1.000 EA
NP1280L	ALUM, UL CSA, W/THERMAL, FARM DUTY,	1.000 EA
G0PA1000	PACKAGING GROUP	1.000 EA

Accessories		
Part Number	Description	Multiplier
37-3301	\ FACE KIT	P1


Performance Data at 230V, 60Hz, 5.0HP (Typical performance - Not guaranteed values)**General Characteristics**


Full Load Torque:	15.1 LB-FT	Start Configuration:	DOL
No-Load Current:	7.48 Amps	Break-Down Torque:	50.0 LB-FT
Line-line Res. @ 25°C.:	0.308 Ohms A Ph / 0.966 Ohms B Ph	Pull-Up Torque:	38.0 LB-FT
Temp. Rise @ Rated Load:	65 C	Locked-Rotor Torque:	62.0 LB-FT
Temp. Rise @ S.F. Load:		Starting Current:	157.0 Amps

Load Characteristics


% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	67.0	84.0	89.0	92.0	94.0	94.0	0.0
Efficiency:	67.8	81.2	84.8	84.9	83.9	82.0	0.0
Speed:	1786.0	1773.0	1757.0	1740.0	1722.0	1700.0	0.0
Line Amperes:	8.77	12.0	15.9	20.7	25.8	31.4	0.0

Performance Graph at 230V, 60Hz, 5.0HP Typical performance - Not guaranteed values





CD0152



	LINE A	LINE B	JOIN
STD	1,8	4	J,5
OPP	1,5	4	J,8

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. OPTIONAL OIL CAPACITOR IS PROVIDED WHEN SPECIFIED.
4. CAPACITORS MAY BE SEPERATELY MOUNTED.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION

REV. LTR: D

VERSION: 01

TDR: 000000373039

ZG10DO

FILE: \AAA\00026\903

REVISED: 11:23:45 08/11/2005

MTL: -

BY: ENJOEPO

BALDOR ELECTRIC Co.

TYPE L OR LC, SV, REV, 5 LDS, THERM, CAPS MAY BE SEP MTD

CD0152