

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure for Disconnect – WM 8017.548

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure for Disconnect – WM 8017.548 - WM242608XC

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:	These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a cold rolled steel body and door, and a zinc plated mounting panel.
Material:	Door: Carbon steel, 2.0 mm, all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel, zinc-plated
Surface finish:	Dipcoat-primed and powder-coated, textured paint
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Flange door with universal disconnect cutout 2-point latching L-Handle

Product features

Dimensions:	Height: 600 mm (24 ") Width: 650 mm (26 ")
--------------------	---

Depth: 210 mm (8.3 ")

Material thickness: Housing: 2 mm (0.08 ")
Door: 2 mm (0.08 ")
Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 570 mm (22 ")
Width: 549 mm (22 ")

Packaging unit: 1 pc(s).

Weight/packaging unit: 27 kg (59.5 lb.)

EAN: 83129

Approvals

Approvals: UL + C-UL
