



Heavy Duty Safety Switch

DH362UDK

UPC:782113206158

Dimensions:

Height: 8.31 INLength: 16.5 INWidth: 9.12 IN

Weight:21 LB

Notes:Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Type: Single-Throw
Amperage Rating: 60A
Enclosure: NEMA 12

• Enclosure Material: Painted galvanized steel

Fuse Configuration: Non-fusible
Number Of Poles: Three-pole
Number Of Wires: Three-wire

• Product Category: Heavy Duty, Non-Fusible

• Voltage Rating: 600V

 Max Hp Rating: 10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 20 at 240 Vac TD 3 Ph, 50 at 480 Vac TD 3 Ph, 60 at 600 Vac TD 3 Ph, 10 at 250 Vdc

Supporting documents:

- Eatons Volume 2-Commercial Distribution
- Drawing Dataset



• Eaton Specification Sheet - DH362UDK

Certifications:

• UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.