

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 – TS 8206.500

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 – TS 8206.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK code:	IK09
Supply includes:	Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting plate 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth
Base material:	Carbon steel

Product features

Dimensions: Height: 2000 mm (79 ")
Width: 1200 mm (47 ")
Depth: 600 mm (24 ")

Mounting plate: Height: 1896 mm (75 ")
Width: 1099 mm (43 ")

Number of doors: 2

2 support strips fitted in the enclosure depth: yes

Packaging unit: 1 pc(s).

Weight/packaging unit: 194.6 kg (429 lb.)

EAN: 4028177250888

Customs tariff number: 94032080

ETIM 6.0: EC000261

ETIM 5.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 7.0/7.1: 27180101

eCl@ss 6.0/6.1: 27180101

eCl@ss 5.1/5.1.4: 27180101

Product description (long): TS Bayed enclosure system, WHD: 1200x2000x600 mm, Sheet steel, with mounting plate, two doors at the front

Approvals

Approvals: Bureau Veritas
CSA
DNV-GL
RRR
Russian Maritime Register of Shipping
TÜV UL + C-UL

Certificates: EAC
IK-Code

Protection category

Declarations:

Declaration of conformity
Manufacturer's declaration
