

Rittal – The System.

Faster – better – everywhere.

Circuit-Breaker Component Adaptors 3-pole – SV 9345.700

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Circuit-Breaker Component Adaptors 3-pole – SV 9345.700

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Color: RAL 7035

Supply includes: Connection straps
Sliding Blocks

Note: Cable outlet: Switch outlet or as outgoing cable from the switchgear
The technical data may vary for UL applications.

Note on Model No.:: The 9342.720 insert strip is also required when using Siemens VL630 switchgear

Product features

Suitable for busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with center-to-center spacing: 60 mm

Dimensions: Height: 345 mm (14 ")
Width: 140 mm (5.5 ")

Rated operating 690 V, 3~

voltage:	
Rated current (max.):	630 A
Cable outlet:	Top
To fit manufacturer (model):	ABB (S5, T5, T5 UL) Allen Bradley (140U-L) Eaton (NZM3, NZM3 UL/630 A) GE (FG630) Legrand (DPX 630) Mitsubishi (NF630-SEW/HEW/REW) OEZ (BH630N, BH630S) Schneider Electric (NS(X)630, NSJ600) Schrack (MC3) Siemens (VL630, 3VA24, 3VT3, 3V10 73, 3RV13 73, 3RV13 74, 3VA64) Terasaki (E630, S630)
Packaging unit:	1 pc(s).
Weight/packaging unit:	3.77 kg (8.3 lb.)
EAN:	4028177680005
Customs tariff number:	85369095
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27400613
eCl@ss 6.0/6.1:	27400613
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Circuit-breaker component adaptor, 630 A, 690 V, 3-pole, cable outlet top, with connection straps

Approvals

Approvals:	ABS DNV-GL UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity