

Catalog Number: BTM0505
Product ID: 7TCA297020R0073
EAN Number: 05011949213906
Status: Active

Fitting for Pliable Conduit, Straight with Internal Female Thread, Conduit Size 25mm, M25 Thread, Very High Mechanical and UV Protection, IP66, IP67 Ratings, Brass to BS2874 with Nylon Seals

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Kopex
Type	Fitting for Pliable Conduit
Special Features	Very High Degree of UV and Mechanical Protection
Application	For Use with Male Threaded Fittings or Rigid Conduits
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Size	Conduit Size 25mm
Material	Brass with Nylon Seals
Insulation Class	IP66, 67
Color	Metallic
Connection	Straight, M25 Thread
Temperature Rating	-40 to 130 Degrees C

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	25mm
Nominal size in inch	3/4 inch
Degree of protection (IP) conduit dependant	IP66-IP67
Model	Straight
Revolving thread	N
Construction type	Internal thread
Thread type	Metric
Thread connection size	M25 x 1.5
One-piece	Y
Material housing	Brass
Surface protection	Untreated
Thread length	17mm
Total length	48mm
Total height	36mm
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	N
Approved in combination with protective conduit FI	N
Operating temperature	-40-+130°C

Packaging

Outer Quantity	10
Outer Dimensions (inches)	1x1x1
Weight Uom	0.58 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com