

**Catalog Number:** BTM0808  
**Product ID:** 7TCA297020R0076  
**EAN Number:** 05011949213937  
**Status:** Active

Fitting for Pliable Conduit, Straight with Internal Female Thread, Conduit Size 50mm, M50 Thread, Very High Mechanical and UV Protection, IP66, IP67 Ratings, Brass to BS2874 with Nylon Seals

#### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Kopex
Type	Fitting for Pliable Conduit
Special Features	Very High Degree of UV and Mechanical Protection
Application	For Use with Male Threaded Fittings or Rigid Conduits
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Size	Conduit Size 50mm
Material	Brass with Nylon Seals
Insulation Class	IP66, 67
Color	Metallic
Connection	Straight, M50 Thread
Temperature Rating	-40 to 130 Degrees C

#### European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	50mm
Nominal size in inch	1 1/2 inch
Degree of protection (IP) conduit dependant	IP66-IP67
Model	Straight
Revolving thread	N
Construction type	Internal thread
Thread type	Metric
Thread connection size	M50 x 1.5
One-piece	Y
Material housing	Brass
Surface protection	Untreated
Thread length	23.2mm
Total length	70mm
Total height	65.5mm
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	N
Approved in combination with protective conduit FI	N
Operating temperature	-40-+130°C

#### Packaging

Outer Quantity	2
Outer Dimensions (inches)	1x1x1
Weight Uom	2.75 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)