

**Catalog Number:** FLT0720  
**Product ID:** 7TCA297020R0189  
**EAN Number:** 05011949214910  
**Status:** Active



Actual

Liquid Tight, Low Fire Hazard Conduit, Nominal Conduit Size 40mm, 1-1/4 Inch US Trade Size, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 20 Meters, Galvanised Steel Core, String Packing with LFH Covering, Black

### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Low Fire Hazard Conduit
Application	Indoors / Outdoors, Marine, Buildings, & Rail Infrastructure Where Low Smoke and Toxicity are of Concern
Standard	BSI Kitemark KM-90009, Low Voltage Directive, London Underground I-085, NFF16-101 (I1 F1)
Trade Size	NC 40mm/1-1/4 Inch
Outside Diameter	41.8mm
Inside Diameter	35.4mm
Length	20 Meters
Radius	180mm
Flexibility	Medium
Material	Galvanized Steel Core with String Packing and Low Fire Hazard Coating
Color	Black

### European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	40mm
Nominal size in inch	1 1/4 inch
Outer diameter	41.8mm
Inner diameter	35.4mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-20-+90°C
Degree of protection (IP)	IP67
Weight	0.946kg/m
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	63.62 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)