

Catalog Number: PHH0430
Product ID: 7TCA297020R0266
EAN Number: 05011949205123
Status: Active

Liquid Tight, Pliable Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.0mm, Inside Diameter 14.6mm, Static Bend Radius 35mm, Reel Length 30 Meters, IP66, IP67 Rating, Galvanized Steel and Kraft Paper Core with Co-Polyester Jacket, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Pliable Conduit
Application	Indoors / Outdoors, Marine, Buildings, Infrastructure
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	NC 20mm/1/2 Inch
Outside Diameter	21.0mm
Inside Diameter	14.6mm
Length	30 Meters
Radius	35mm
Material	Galvanized Steel with Kraft Paper Core and Co-Polyester Jacket
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Outer diameter	21mm
Inner diameter	14.6mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Polyester
Operating temperature	-50-+130°C
Degree of protection (IP)	IP67
Weight	0.484kg/m
Colour	Black
Bending strength	Pliable
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	30.95 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com