

**Catalog Number:** PHH0620  
**Product ID:** 7TCA297020R0269  
**EAN Number:** 05011949205161  
**Status:** Active

Liquid Tight, Pliable Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Outside Diameter 34.0mm, Inside Diameter 26.7mm, Static Bend Radius 55mm, Reel Length 20 Meters, IP66, IP67 Rating, Galvanized Steel and Kraft Paper Core with Co-Polyester Jacket, Black

#### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Pliable Conduit
Application	Indoors / Outdoors, Marine, Buildings, Infrastructure
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	NC 32mm/1 Inch
Outside Diameter	34.0mm
Inside Diameter	26.7mm
Length	20 Meters
Radius	55mm
Material	Galvanized Steel with Kraft Paper Core and Co-Polyester Jacket
Color	Black

#### European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Outer diameter	34mm
Inner diameter	26.7mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Polyester
Operating temperature	-50-+130°C
Degree of protection (IP)	IP67
Weight	1.153kg/m
Colour	Black
Bending strength	Pliable
Approved according to DIN EN 61386-23 Y	

#### Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	49.42 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)