

**Catalog Number:** PHT0310  
**Product ID:** 7TCA297020R0284  
**EAN Number:** 05011949004610  
**Status:** Active

Liquid Tight, Pliable Conduit, Nominal Conduit Size 16mm, 3/8 Inch US Trade Size, Outside Diameter 17.8mm, Inside Diameter 11.6mm, Static Bend Radius 35mm, Reel Length 10 Meters, IP66, IP67 Rating, Galvanized Steel and Kraft Paper Core with Low Fire Hazard Jacket, Black

#### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Pliable Conduit
Application	Indoors / Outdoors, Marine, Buildings, & Rail Infrastructure Where Low Smoke and Toxicity are of Concern
Standard	BSI Kitemark KM-90009, Low Voltage Directive, London Underground I-085, NFF16-101 (I1 F1)
Trade Size	NC 16mm/3/8 Inch
Outside Diameter	17.8mm
Inside Diameter	11.6mm
Length	10 Meters
Radius	35mm
Material	Galvanized Steel with Kraft Paper Core and Low Fire Hazard Coating
Color	Black

#### European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	16mm
Nominal size in inch	3/8 inch
Outer diameter	17.8mm
Inner diameter	11.6mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-25-+90°C
Degree of protection (IP)	IP67
Weight	0.375kg/m
Colour	Black
Bending strength	Pliable
Approved according to DIN EN 61386-23 Y	

#### Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	7.44 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: techsupport@tnb.com