

**LED T8 Retrofits - Compatible - Glass Tube**

**Models**
**LED-6204-4-XXK-G2, 17W, 120-277VAC, cETLus, 4000K & 5000K CCT. Ballast Compatible**
**Description**

Light Efficient Design's T8 retrofits provide an efficient and reliable retrofit for 4 foot T8 lamps. These lamps are designed as a replacement for a 32 watt Fluorescent lamps. Ballast compatible lamps allow for easy Plug and Play installation.

**Features**

- Glass tube T8 are available for Plug and Play installation
- Up to 2,200 lumen output and 130 LPW efficacy.
- G13 base, fits standard 4 foot T8 light fixtures.
- ETL approved for damp environments and enclosed fixtures.
- 50,000 hour rated LED life
- 5 Year Limited Warranty - see website for details



Actual Product may vary slightly from photo.


**TECHNICAL SPECIFICATIONS - USA 120-277V - ALL MODELS cULus**

MODEL	VOLTAGE	WATTAGE	LUMENS*	LPW*	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-6204-4-40K-G2	Ballast Only	17W	2200	128	32W T8	G13	4000K	>80	<20%	.99	0	0	220°	No
LED-6204-4-50K-G2	Ballast Only	17W	2200	128	32W T8	G13	5700K	>80	<20%	.99	0	0	220°	No

**PACKAGING SPECIFICATIONS**

MODEL	PRODUCT DIMENSION	PRODUCT WEIGHT	UNIT CARTON DIMENSION	UNIT CTN WT	SHIPPER CARTON DIMENSION	SHIPPER CTN WT	CARTON QUANTITY
LED-6XX4-4-XXK-G2	47.2 x 1.125 in. 1199 x 29 mm.	1 lbs	48 x 1.3 x 1.3 in. 1219 x 33 x 33 mm	1 lbs/.45 kg.	49.6 X 7.4 X 7.3 in./ 1260 X 188 X 185 mm.	22 Lbs/10 kg.	20

**UPC / UCC**
**DESIGN LIGHTS CONSORTIUM QPL CERTIFICATION SUMMARY**

MODEL	PRODUCT UPC	CARTON UCC	QPL CATEGORY 1	PRODUCT CODE	FAMILY CODE	QPL CATEGORY 2	PRODUCT CODE	FAMILY CODE
LED-6204-4-40K-G2	844006064334	10844006064331	Linear Replacement Lamp	PL8RXHF8MNUO	NANPEW	0	0	0
LED-6204-4-50K-G2	844006064341	10844006064348	Linear Replacement Lamp	PLCHU17L7SUD	NANPEW	0	0	0

**ENERGY SAVINGS vs. FLUORESCENT**

LED Lamp Power (watts)	17
Fluorescent Lamp Power (watts)	32
Ballast Power (watts)	4.8
Total power Savings (watts)	19.8
Annual Energy Savings	\$ 11
Lifetime Energy Savings over 50,000 hrs)	\$ 109

**THERMAL SPECIFICATIONS**

OPERATING TEMPERATURE	-40°F - +122°F
-----------------------	----------------