



Revision Number: 004.0

Issue date: 08/29/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8040 PENETRATING OIL **IDH number:** 996456
 known as LOCTITE® FREEZE & RELEASE Part
Product type: Rust dissolver **Item number:** 996456
Restriction of Use: None identified **Region:** United States
Company address: **Contact information:**
 Henkel Corporation Telephone: (860) 571-5100
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center
 Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.
 FLAMMABLE AEROSOL.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.
 CAUSES DAMAGE TO ORGANS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a poison center or physician. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

IDH number: 996456

Product name: LOCTITE LB 8040 PENETRATING OIL known as LOCTITE® FREEZE & RELEASE Part

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Norflurane	811-97-2	30 - 60
n-Heptane	142-82-5	10 - 30
Butane	106-97-8	10 - 30
Kerosine (petroleum), hydrodesulfurized	64742-81-0	5 - 10
Propane	74-98-6	1 - 5
Methanol	67-56-1	1 - 5

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
Skin contact:	Wash affected area immediately with soap and water. If skin irritation persists, call a physician.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Do not puncture or incinerate pressurized containers.

Hazardous combustion products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Wipe up with adsorbent material (e.g. cloth, fleece). Store in a partly filled, closed container until disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray. Wash thoroughly after handling. Keep container closed.

Storage: Keep in a cool, well ventilated area. Store away from heat, sparks, flames, or other sources of ignition. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Norflurane	None	None	1,000 ppm (4,240 mg/m ³) TWA	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m ³) PEL	None	None
Butane	1,000 ppm STEL	None	None	None
Kerosine (petroleum), hydrodesulfurized	200 mg/m ³ TWA (as total hydrocarbon vapor) Non-aerosol. (SKIN) (as total hydrocarbon vapor) Non-aerosol.	None	None	None
Propane	Included in the regulation but with no data values. See regulation for further details	1,000 ppm (1,800 mg/m ³) PEL	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m ³) PEL	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol, Liquid
Color:	Colorless
Odor:	Kerosene
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	> 37.0 °C (> 98.6 °F)
Melting point/ range:	Not available.
Specific gravity:	0.72
Vapor density:	Not available.
Flash point:	Not applicable to aerosols. But liquid contents will burn if exposed to an ignition source. Not flammable by flame extension method.
Flashback:	This product exhibits no flashback when tested for flame extension.
Flame projection:	0.00 cm (0inch)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 50 %; 423 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Extremes of temperature and direct sunlight.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. May cause central nervous system effects with nausea, dizziness and headache.
Skin contact: Causes skin irritation.
Eye contact: Causes serious eye irritation.
Ingestion: Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Norflurane	None	Cardiac, Central nervous system, Irritant, Respiratory, Skin
n-Heptane	Inhalation LC50 (Rat, 4 h) = 103 mg/l	Central nervous system, Irritant
Butane	Inhalation LC50 (Rat, 4 h) = 658 mg/l	Cardiac, Central nervous system, Irritant
Kerosine (petroleum), hydrodesulfurized	None	Irritant
Propane	None	Cardiac, Central nervous system, Irritant
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg Inhalation LC50 (Rat, 4 h) = 64000 ppm	Eyes, Irritant, Metabolic, Nervous System

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Norflurane	No	No	No
n-Heptane	No	No	No
Butane	No	No	No
Kerosine (petroleum), hydrodesulfurized	No	No	No
Propane	No	No	No
Methanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, non-flammable
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (n-Heptane)
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None
Marine pollutant: n-Heptane

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Fire, Immediate Health, Delayed Health, Pressure
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methanol (CAS# 67-56-1).
CERCLA Reportable quantity: n-Heptane (CAS# 142-82-5) 100 lbs. (45.4 kg)
Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)
Butane (CAS# 106-97-8) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Timothy Pratt, Regulatory Affairs Specialist

Issue date: 08/29/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.