

DSN37c
DS37c



DSN37c Multipin – 7.5A Plugs & Receptacles

Ratings

- **Voltage**
Up to 480 VAC Max/130 VDC
- **Amperage Rating**
2A Current Interrupting
7.5A Non-Current Interrupting
! DSN37c/DS37c is capable of handling 4-20mA low current applications
- **Environmental Ratings**
IP66/IP67
- **Temperature Range**
Min -40°F/Max 140°F
See pg 234 for temps below -15°F.
- **Wiring Capacity**
Min 18 AWG Max 14 AWG
- **Applicable Standards**
UL Coming Soon!

For DSN37c dimensions, see pgs 35-36

Receptacle (female)



Don't forget to add installation accessories to your order

Inlet (male)



North American Configurations

Voltage	Polarity	DSN37c Part # Poly	DS37c Part # Stainless Steel	Voltage	Polarity	DSN37c Part # Poly	DS37c Part # Stainless Steel
50V	37P*	63-C4003	37-C4003-SS	50V	37P*	63-C8003	37-C8003-SS
480V	36P+G*	63-C4003	37-C4003-SS	480V	36P+G*	63-C8003	37-C8003-SS

+ 37P for devices up to 50V or 36P+G for devices up to 480V. Multiple voltage labels are provided for application in the field.

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800.433.7642.

Highlighted Feature

- **Crimped Contacts**
DSN37c devices now feature contacts that can be crimped or soldered. Each device is supplied with 3 bags of 13 contacts so that the product can be set up to suit application needs.

Simple Assembly and Disassembly



Assembly

To insert contacts when they have been wired is simple. Push wired contact into rear of insulator until it stops to complete the installation.



Disassembly

To remove, use the tool provided. Push tool from front onto contact until tool stops. Contact is then released at rear of insulator.

Main Options



Padlock Pawl



Mushroom Pawl



Self-Ejecting Devices*

* Requires straight insertion receptacle or inlet and self-ejecting plug or connector

Receptacle Options

Part

Straight Insertion	Recept # - 352
Self-Ejecting Connector Release	Recept # - 354
Mushroom Pawl	Recept # - 375
Padlock Pawl	Recept # - 843
Padlockable Mushroom Pawl	Recept # - 375- 843
Closed Lid Configuration	Recept # - NC



See pgs 211-220 for detailed information on these options

Inlet Options

Part

Self-Ejecting Plug Release	Inlet # - 338
----------------------------	---------------

Poly Devices Only

DSN37c Order Example:

To order a device with a Mushroom Pawl add **-375** to the receptacle part number.

DSN37c 32P = 63-C4003-**375**

Installation Accessories

Handles



NPT	Poly Handle	Stainless Steel Handle
1/2"	61-6A013-12	
3/4"	61-6A013-34	3H34SS
1"	61-6A013-1	3H1SS
1 1/4"	61-6A013-114	3H114SS



Makes connector closures easier

Cable Range	Poly Handle w/Clamp & Bushing	Nylon Handle	Poly Handle w/built in Draw Grips
.32 - 1.25	-	-	61-6A473
.39 - 1.18	-	61-6A013	-
.750 - .875	3PM514	-	-
.875 - 1.000	3PM516	-	-
1.000 - 1.125	3PM518	-	-
1.125 - 1.250	3PM520	-	-
1.250 - 1.375	3PM522	-	-

- Notes:**
- Finger draw plates are recommended for easier connector closure on cord to cord assemblies.
 - For available cord grips see pgs 169-170.

Angles



Nylon 30° Angle	Metal 30° Angle	Metal 70° Angle	Metal Angle FS/FD Box 30°	Metal Straight Adapter	Stainless Steel 30° Angle
61-6A027	MA3	89-3A027	MAFS3*	MS3	MA3SS



* MAFS3 base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.

NPT Guidelines

Cable Range	NPT
.312 - .625	1/2"
.438 - .812	3/4"
.660 - 1.000	1"
.875 - 1.375	1 1/4"

NPT sizes are determined by the cable diameter and third party cord grip.

Junction Boxes



NPT	Metal Box	Metal Box with Nylon Angle	Stainless Steel Box*** w/Stainless Steel Angle	Poly* Conduit Entry	Poly 70°** Wall Box	Poly 70° Alum Wall Box	Stainless Steel Box
1/2"	MB312	61-6A053-080-12	-	61-6A023-12	51-CA058	59-CA058-12	-
3/4"	MB334	61-6A053-080-34	-	61-6A023-34	51-CA058	59-CA058-34	-
1"	MB31	61-6A053-080-1	39-3A053-080-SS-1	61-6A023-1	51-CA058	59-CA058-1	MB31SS
1 1/4"	MB3114	61-6A053-080-114	-	-	51-CA058	59-CA058-114	-
1 1/2"	-	-	-	-	-	59-CA058-112	-

* For poly devices only.

** 70° boxes are not drilled. Contact customer service if factory drilling is required.

*** Includes angle adapter as shown.

+ Interior volume with receptacle installed.

Miscellaneous Accessories



* Set of Two (2)



For Male Devices Only



For Male Devices Only



Receptacle+ Lockout Pin



Multi-Contact Removal Tool



Crimper Tool (Greenlee or equal)



European Crimping Tool

* Recommended for cord to cord assembly applications, for easier connector closure.

+ Requires Padlockable Pawl option (-843) on receptacle.