



## Catalog No. R038CP4033

Description: 100A POST MTRD 20/20GFCI/20GFCI

UPC No 784567208146

## Home > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors	
Category	Power Outlets & Temporary Power
Specifications	
Mounting	Galvanized Steel Pad Mount Post
Heads	1
Metering	Ringless
Receptacles	6-20R, (2) 5-20R2GFCI
Feed	Underground
AIC	10,000
Amps	100.0 A
Circuit Protection	Yes
Hub Provision	No
Installed Breaker	GFI220, (2) CB120, SPACE CB120
Load Center	LC33N1
Loop Feed	Yes
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	45.0 lb
Volts	120/240
Classifications	
Standard Package	1
Stock Class Code	Non Stock
Approvals	
Certification	UL/CUL

midwestelectric.com Created on: 07/31/2018