



Catalog No. U038G033

Description: 100A SURFACE UNMTRD 20 (2)20GFCI

UPC No 784567301090

Home > Power Outlets & Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors Category Power Outlets & Temporary Power

Specifications	
Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	6-20R, (2) 5-20R2GFCI
Feed	Overhead
AIC	10,000
Amps	100.0 A
Cabinet Size	9 X 17
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	GFI220, (2) GFI120
Load Center	LC55N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	15.0 lb
Volts	120/240

Classifications	
Standard Package	1
Stock Class Code	Non Stock

Approvals	
Certification	UL/CUL

midwestelectric.com Created on: 07/26/2018

Publications		
Title	Publication No.	Publication Type
U038G033 Outline Drawing		Drawings-Outline and Dimensional
U038G033 Outline Drawing	265A6223SH52	

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

midwestelectric.com Created on: 07/26/2018