

## DESCRIPTION

- Chrome plated metal construction
- Pressure balancing cycle valve design with 1/4 turn stops
- 3 function transfer valve with 1/2" CC connections
- Contains: hand-held shower with non-positive pause, 69" metal hose, 30" slide bar, drop ell, and tub filler
- **Slide bar is NOT DESIGNED TO BE A GRAB BAR**
- Applicable components are supplied with vandal resistant screws

## OPERATION

- Temperature and transfer valves both have ADA compliant lever style handles
- Temperature handle operates counterclockwise through a 270° arc with off at 6 o'clock, and the maximum hot at the 9 o'clock position
- Adjustable temperature limit stop
- Pressure balancing mechanism maintains selected discharge temperature to ± 2°
- Transfer valve operates 3 distinct functions

## FLOW

- 2.5 gpm (9.5L/min) hand-held shower

## CARTRIDGE

- 1222HD brass cartridge design in temperature control valve accommodates back to back installations
- Brass construction with stainless steel materials
- Ceramic disc cartridge in transfer valve


## STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- Backflow prevention compliance through ASME A112.18.3

- **ADA** for lever handles

## WARRANTY


- Warranted for 5 years against material or manufacturing defects



## Three-Function Commercial Tub/Shower System



Model: 8341



NOTE: This valve is not intended to be used as a shut-off valve. To prevent the potential of cross flow, check valves must be integral to the supply valve or installed in both hot and cold water supply lines.

## CRITICAL DIMENSIONS

(DO NOT SCALE)