

**MINITERMS**

**Male & Female Plugs  
Plier Tap and Pin Terminal,  
Male/Female Adapter**  
PM, PF, PTC, PT SERIES

**FEATURES**

**UN-INSULATED/  
NYLON:**

Electro tin plated copper, nylon  
600V, 75 °C.

**UN-INSULATED/  
NYLON:**

Female plug style with safety &  
reliability.

Electro tin plated copper, easy-entry  
Nylon, 600V, 105 °C.

**VINYL:**

Insulation piercing tap.

Electro tin plated copper with brazed  
seam, Vinyl (PVC), 600V, 75 °C

**VINYL:**


Pin terminal style designed for use in  
terminal blocks.

Electro tin plated copper with brazed  
seam, 600V, 105 °C.

**UN-INSULATED:**

Similar tongue style to a spade,  
black spades have longer, flatter  
sides designed for use in terminal  
blocks.

Brass, Quick disconnect, Easy-entry,  
600V, 105 °C.



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Plugs Male	Un-insulated	22-18	0.157	NON-UL
Plugs Male	Un-insulated	16-14	0.157	NON-UL
Plugs Male	Nylon	22-18	0.157	UL
Plugs Male	Nylon	16-14	0.157	UL
Plugs Female	Un-insulated	22-18	0.157	NON-UL
Plugs Female	Un-insulated	16-14	0.157	NON-UL
Plugs Female	Nylon	22-18	0.157	UL
Plugs Female	Nylon	22-18	0.157	NON-UL
Plugs Female	Nylon	16-14	0.157	UL
Plugs Female	Nylon	16-14	0.157	NON-UL
Plugs Female	Nylon	16-14	0.197	NON-UL
Plier Tap Connector	Vinyl	22-18	n/a	
Plier Tap Connector	Vinyl	16-14	n/a	
Plier Tap Connector	Vinyl	12-10	n/a	
Pin Terminal	Vinyl	22-18	n/a	
Pin Terminal	Vinyl	16-14	n/a	
Pin Terminal	Vinyl	12-10	n/a	
Male Female Adapter	Un-insulated	n/a	0.250	
Male Female Adapter	Un-insulated	n/a	0.250	

MINITERMS



		"S" PACKS		PRO PACKS		STD PACKS		BULK PACKS	
L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.630	0.145	–	---	---	---	<b>PM22-157</b>	100	<b>PM22-157-BULK</b>	1000
0.630	0.136	–	---	---	---	<b>PM16-157</b>	100	<b>PM16-157-BULK</b>	1000
0.890	0.145	–	---	---	---	<b>PM22-157N</b>	100	<b>PM22-157N-BULK</b>	1000
0.890	0.145	–	---	---	---	<b>PM16-157N</b>	100	<b>PM16-157N-BULK</b>	1000
0.680	0.194	–	---	---	---	<b>PF22-157</b>	100	<b>PF22-157-BULK</b>	1000
0.680	0.185	–	---	---	---	<b>PF16-157</b>	100	<b>PF16-157-BULK</b>	1000
1.000	0.128	–	---	---	---	<b>PF22-157N</b>	100	<b>PF22-157N-BULK</b>	1000
1.234	0.309	–	---	---	---	<b>PFS22-157N</b>	100	<b>PFS22-157N-BULK</b>	1000
1.000	0.150	–	---	---	---	<b>PF16-157N</b>	100	<b>PF16-157N-BULK</b>	1000
1.233	0.339	–	---	---	---	<b>PFS16-157N</b>	100	<b>PFS16-157N-BULK</b>	1000
1.233	0.339	–	---	---	---	<b>PFS16-197N</b>	100	<b>PFS16-197N-BULK</b>	1000
0.790	0.550	–	---	---	---	<b>PTC22-18</b>	100	<b>PTC22-18-BULK</b>	500
0.790	0.550	–	---	---	---	<b>PTC16-14</b>	100	<b>PTC16-14-BULK</b>	500
0.800	0.740	–	---	---	---	<b>PTC12-10</b>	50	<b>PTC12-10-BULK</b>	250
0.930	0.078	–	---	---	---	<b>PT-22V</b>	100	<b>PT-22V-BULK</b>	1000
0.930	0.078	–	---	---	---	<b>PT-16V</b>	100	<b>PT-16V-BULK</b>	1000
1.120	0.107	–	---	---	---	<b>PT-12V</b>	50	<b>PT-12V-BULK</b>	500
0.825	0.564	–	–	---	---	<b>250-3-Z</b>	100	<b>250-3-Z-BULK</b>	1000
0.825	0.564	<b>DMT250-3-S</b>	15	<b>DMT250-3-P</b>	60	<b>DMT250-3</b>	100	<b>DMT250-3-BULK</b>	1000