

MINITERMS

Spade Terminals

S Series Cont'd

SPECIFICATIONS

- Nylon: Electro tin plated copper, Nylon, 600V, 105 °C.

FEATURES

- Nylon Spade Terminal have open tongue end for rapid insertion on the mounting screw. Typically used on free-standing studs.

FIG. 3



FIG. NO.	INSULATION TYPE	WIRE RANGE	STUD SIZE	RATINGS	LENGTH (L) (IN.)	WIDTH (W) (IN.)	SEAM TYPE	STD PACKS		BULK PACKS	
								CAT. NO.	QTY	CAT. NO.	QTY
3	Nylon	22-18	#10	UL	0.727	0.187	Butted	S22-10N	100	S22-10N-BULK	1000
3	Nylon	22-18	#4	UL	1.031	0.319	Butted	S22-4N	100	S22-4N-BULK	1000
3	Nylon	22-18	#6	UL	0.898	0.286	Butted	S22-6N	100	S22-6N-BULK	1000
3	Nylon	22-18	#8	UL	1.022	0.472	Butted	S22-8N	100	S22-8N-BULK	1000
3	Nylon	16-14	1/4	—	0.898	0.338	Butted	S16-14N	100	S16-14N-BULK	1000
3	Nylon	16-14	#10	cULus	0.855	0.255	Butted	S16-10N	100	S16-10N-BULK	1000
3	Nylon	16-14	#6	cULus	0.855	0.286	Butted	S16-6N	100	S16-6N-BULK	1000
3	Nylon	16-14	#8	cULus	1.221	0.476	Butted	S16-8N	100	S16-8N-BULK	1000
3	Nylon	12-10	1/4	cULus	1.024	0.375	Butted	S12-14N	50	S12-14N-BULK	500
3	Nylon	12-10	#10	cULus	1.000	0.336	Butted	S12-10N	50	S12-10N-BULK	500
3	Nylon	12-10	#6	cULus	1.000	0.375	Butted	S12-6N	50	S12-6N-BULK	500
3	Nylon	12-10	#8	cULus	1.256	0.474	Butted	S12-8N	50	S12-8N-BULK	500
3	Nylon	8	1/4	—	1.256	0.474	Butted	S8-14N	50	S8-14N-BULK	500
3	Nylon	8	#10	—	1.256	0.474	Butted	S8-10N	50	S8-10N-BULK	500