

EY 25% * Fill Vertical Sealing Fittings for Close Turning Radius


Explosionproof, Dust-Ignitionproof, Raintight

For Use with Threaded Rigid Metal Conduit and IMC.


NEC/CEC:

Class I, Division 1 and 2, Groups A[◇], B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

		Millimeters (Inches)			Kwiko™ A Cement Required Grams (Ounces)	Catalog Number Grayloy™ Iron
		Trade Size (Inches)	A (Length)	B (Width)	Turning Radius ①	
EY Vertical Sealing Fittings (25% fill)						
		Female				
		1/2	3-1/4	1-3/16	1-1/8	2 EY-50
		3/4	3-5/8	1-1/4	2-3/8	3 EY-75
		1	4-1/4	1-3/8	2-3/4	5 EY-100
		1-1/4	5-1/16	2-15/16	2	11 EY-125
		1-1/2	5-1/2	2-1/2	3-1/2	19 EY-150
		2	6-1/4	2-1/8	3-15/16	31 EY-200
Female Male						
Male/Female (Removable Male Nipple)						
		1/2	4-15/16	1-3/16	1-1/8	2 EYM-50
		3/4	5-19/64	2-1/4	1-3/8	3 EYM-75
		1	6-1/32	2-3/8	1-3/4	5 EYM-100
		1-1/4	5-13/16	2	2-5/8	6 EYM-125
		1-1/2	6-1/4	2-1/4	3	9 EYM-150
		2	7	2-3/4	3-5/8	15 EYM-200



Type EY



Type EYM

* Per NEC 501.15(C)(6), seals in Class I, Division 1 and 2 must be limited to conductor fill of 25% of cross sectional area of a rigid metal conduit of the same trade size unless approved for higher percentage fill. See 40% fill sealing fittings.

① Turning radius with cover or plug removed.

◇ Indicates items in the shaded area which are UL Listed for Class I, Groups A, B, C, D; Class II, Groups E, F, G; and Class III.