

GUA Conduit Outlet Box Covers

For Pendent Mounting Fixtures. Explosionproof, Dust-Ignitionproof

UNILETS™ for use with Threaded Metal Conduit. Furnished with Internal Ground Screw and O-ring.

NEC/CEC:

Class I, Division 1 and 2, Groups C, D
Class I, Zone 1 and 2, Groups IIA, IIB
Class II, Division 1 and 2, Groups E, F, G
Class III

Applications

- Provides NPT thread hub for mounting pendant light fixtures (luminaires) on 1/2", 3/4" and 1" trade size Type GUA outlet boxes.
- Provides additional wiring space and NPT threaded hub for mounting pendant light fixtures (luminaires) on 1/2", 3/4" and 1" trade size Type GUA outlet boxes.

Features

- O-ring gasket provided to assure watertightness.
- Increases internal wiring volume (12.5 cu. in.).
- Side port allows access to conductors after fixture is mounted.
- Tapered threaded hub (NPT).
- Provided with anti-rotation set-screws.
- Maximum weight capacity: 22.7 kg (50 lbs.) per NEC Section 314-27(B).

Standard Materials

- Bodies: malleable Iron
- Screws: steel set screws
- O-ring: buna-n

Standard Finishes


- Bodies: zinc electroplate

Options


- Hot dip or mechanical galvanized. Add suffix **-G** to standard catalog number. Contact your local representative for pricing and availability.

NEC/CEC Certifications and Compliances


- UL Standard: 886
- UL Listed: E-97032
- CSA Standard: C22.2 No. 30
- CSA Certified: 020945
- Fed. Spec: A-A-50563
- NEC Articles 500-503 and 505



Type GUAHC



Type GUAFC




GUA Conduit Outlet Box Covers

For Pendent Mounting Fixtures. Explosionproof, Dust-Ignitionproof



UNILETS™ for use with Threaded Metal Conduit. Furnished with Internal Ground Screw and O-ring.

NEC/CEC:

Class I, Division 1 and 2, Groups C, D
Class I, Zone 1 and 2, Groups IIA, IIB
Class II, Division 1 and 2, Groups E, F, G
Class III

	Hub Type	Conduit Size (Inches)	Catalog Number
	GUAHC	1/2	GUAHC-50
		3/4	GUAHC-75
	GUAFC	1/2	GUAFC-50
		3/4	GUAFC-50

Dimensions in Millimeters (Inches)

Dimensions in Millimeters (Inches)			
Hub Size (Inches)	A	B	C Max. Dia
GUAHC			
1/2	41.4 (1.63)	—	88.9 (3.50)
3/4	41.4 (1.63)	—	88.9 (3.50)
			
GUAFC			
1/2	—	41.4 (1.63)	88.9 (3.50)
3/4	—	41.4 (1.63)	88.9 (3.50)
			

02GEDNEY

ENCLOSURES AND JUNCTION BOXES: NEC/CEC EXPLOSIONPROOF ENCLOSURES

GUA Conduit Outlet Box Covers

Sealing Cover

NEC/CEC:
Class I, Division 1 and 2, Groups C, D
Class I, Zone 1 and 2, Groups IIA, IIB
Class II, Division 1 and 2, Groups E, F, G
Class III

Applications

- Converts 1/2", 3/4" and 1" trade size Type GUA malleable iron outlet boxes into 25% fill sealing fittings.

Features

- Removable plug for pouring sealing compound.
- O-ring gasket provided to assure watertightness.
- Can be used with O-Z/Gedney EYC sealing compound.

Standard Materials

- Body: malleable iron
- Screws: steel set screws
- O-ring: buna-n

Standard Finishes



- Body: zinc electroplated

Options

- Hot dip or mechanical galvanized. Add suffix **-G** to standard catalog number. Contact your local representative for pricing and availability.

NEC/CEC Certifications and Compliances

- UL Standard: 886
- UL Listed: E-97032
- CSA Standard: C22.2 No. 30
- CSA Certified: 020945
- NEC Articles 500-503 and 505
- Fed. Spec: A-A-50563



Dimensions in Millimeters (Inches)		
Turning Radius R	Maximum Body Height A	Catlog Number
63.5 (2.5)	44.5 (1.75)	GUASC-1

GUA Conduit Outlet Box Covers

Threaded Extension

NEC/CEC:
 Class I, Division 1 and 2, Groups C, D
 Class I, Zone 1 and 2, Groups IIA, IIB
 Class II, Division 1 and 2, Groups E, F, G
 Class III

Applications

- Provides for increased internal wiring volume in 1/2", 3/4" and 1" trade size in Type GUA malleable iron outlet boxes

Features

- O-ring gasket provided to assure watertightness.
- Cast-in brackets for use with breaker bar tools.
- Increases internal wiring volume by 11 cu. in.

Standard Materials

- Cover: malleable iron
- O-ring: buna-n

Standard Finishes


- Cover: zinc electroplate

Options

- Hot dip or mechanical galvanized. Add suffix **-G** to standard catalog number. Contact your local representative for pricing and availability.

NEC/CEC Certifications and Compliances

- UL Standard: 886
- UL Listed: E-97032
- CSA Standard: C22.2 No. 30
- CSA Certified: 043437
- NEC Articles 500-503 and 505
- Fed. Spec: A-A-50563



Dimensions in Millimeters (Inches)			
A	Maximum Diameter B	Volume (in³)	Catalog Number
69.9 (2.75)	88.9 (3.5)	11	GUADC-1