



**Flexible Conduits & Fittings**

**T&B Catalog Number:**

ALND-M202

**UPC Number:**

78620994310

**Status:**

Active

**Description:**

Smart Line straight black connector with integral cone seal. Material polyamide 6, thread size - M20 x 1.5.

**Application**

Machine building, installation and construction industries

**Characteristics**

- Easy push-in installation
- Easy re-opening with screwdriver
- Space savings due to compact design
- Self-extinguishing, free of halogens and cadmium
- Excellent impact strength
- Fits both conduit profiles - fine (T) and coarse (G)

**General**

|                       |                                 |
|-----------------------|---------------------------------|
| Material              | Polyamide 6                     |
| Color                 | Black                           |
| Thread Type           | Metric                          |
| Suitable for Use With | PMA Smart Line Conduit, PMAFLEX |

**Dimension Information**

|                               |           |
|-------------------------------|-----------|
| Fits to Conduit Size (NW)     | 12        |
| Fits to Conduit Size (metric) | 16        |
| Fits to Conduit Size (inches) | 3/8       |
| Thread Length (mm)            | 11.0      |
| Thread Size (Metric)          | M20 x 1.5 |

**Technical Information**

|  |                           |
|--|---------------------------|
| Temperature Range-Continuous (Celsius) | -40&deg; C to +105&deg; C |
| Temperature-Short-Term (Celsius)       | +150&deg; C               |
| Technical Data Sheet                   | Available on Website      |
| Chemical Resistance Chart              | Available on Website      |

**Specifications**

|         |                      |
|---------|----------------------|
| 3dmodel | Available on Website |
|---------|----------------------|

**IP Ratings**

|           |                        |
|-----------|------------------------|
| IP Rating | IP66 stat. / IP54 dyn. |
|-----------|------------------------|

**Packaging**

|                    |                |
|--------------------|----------------|
| T&B Inner Pack     | 100            |
| Package in Units   | 800            |
| T&B Sold in UOM    | Each           |
| T&B Weight Per UOM | 0.01 lbs. Each |

**Application Support**

|  |                      |
|--|----------------------|
| PMA Reference Guide                    | Available on Website |
| Conduit Guide-Smart Line               | Available on Website |
| Product Overview-Smart Line Conduits   | Available on Website |
| Product Overview-Smart Line Connectors | Available on Website |
| Product Overview-System Supports       | Available on Website |

Product Overview-PMAFIX Connectors Available on Website

## Certifications

RoHS Compliance Yes

## Certifications



### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com