

Divisible-System Nylon Flexible Accessories

FH System Supports

- Use in machine building and plant construction
- High-grade, specially formulated polyamide 6
- Very high impact resistance
- Optimal axial strain relief due to integrated rib
- Quick installation due to single-hole fixing
- For increased stress due to heavy cables and wires, closing with cable tie is possible
- Very good chemical properties
- Free from halogens and cadmium
- Fits to rail system supports FHS



Temperature range: -40° C to 105° C;
Short term to 160° C

Cat. No. Black	Fixing Screw	Fits to Conduit Size Coflex NW	Dimensions (mm) Width x Length x Depth
BFH-09	M5	10	20 x 19 x 23
BFH-01	M5	14	20 x 24 x 27
BFH-20	M6	20	20 x 35 x 40
BFH-23	M6	23	20 x 43 x 45.5
BFH-37	M6	37	20 x 52 x 52
BFH-48	M6	45	20 x 66 x 66

GB Tube Clamps

- For the mounting of static conduits
- Galvanized steel according to DIN 3016
- Elastomer profile (EPDM), free from halogens
- Smooth connection to PMAFLEX® corrugated conduits
- Good ozone and aging resistance



Temperature range: -50° C to 105° C
Chemical resistance: Very good weather, ozone- and aging resistance; resistant to mineral oils and fats

Cat. No. Black	Fits to Conduit Size		Fits to Conduit Size Coflex NW	Dimensions Width (mm)
	NW	Metric		
SGB-09	10	12	10	13.0
SGB-14	—	—	14	
SGB-20	—	—	20	
SGB-23	—	—	23	
SGB-36	36	40	37	19.0
SGB-48	48	50	45	