


Accessories for Nylon Flexible Conduits

GPS One-Piece System Supports

- For cable protection systems in a wide range of applications
- High-grade, specially formulated polyamide 6
- One-piece construction, stackable
- Excellent impact resistance
- Heavy design, high retention forces
- Applicable with standard metal C rails
- Easy pre-installation by conduit snap-in
- Clasp for easy pre-mounting and final assembly
- Very good chemical properties
- Free from halogens and cadmium
- Fits fine (T) conduit profile
- The following nominal widths can be combined for stacking:
NW 17 with NW 23, NW 29 with NW 36,
NW 48 with NW 56



Cat. No. Fine Profile	Fits to Conduit Size			Dimensions (mm)		
	NW	Metric	DIN-NW	Width	Height	Depth
BGPS-17	17	20	2	70.0	51.0	30.0
BGPS-23	23	25				
BGPS-29	29	32	3	85.0	65.0	
BGPS-36	36	40				
BGPS-48	48	50	4	115.0	92.5	
BGPS-56	56	—				

Temperature range: -40 to 105 °C

Short term: Max. 160 °C

Content of delivery:

System supports with two (2) screws for securing the lid (optional).

Mounting accessories not included

GP System Supports for Stacking

- For cable protection systems in a wide range of applications
- High-grade, specially formulated polyamide
- Variable stacking possibilities — due to the block system, a high rigidity is guaranteed
- Strain relief due to gripping around conduit
- Especially suitable for dynamic applications due to rounded edges
- Variety of support possibilities
- Self extinguishing, free from halogens and cadmium
- Excellent impact strength



Cat. No.	Cat. No.	Conduit Size		Dimensions (mm)		
Fine Profile	Coarse Profile	NW	Metric	Width	Height	Depth
GP-16T	GP-16G	17	20	47.5	66.0	36.0
GP-21T	GP-21G	23	25			
GP-29T	GP-29G	29	32	61.5		
GP-36T	GP-36G	36	40			
GP-48T	GP-48G	48	50	76.0	78.0	
—	GP-56G	56	—	87.0		

— = Insert "B" to order black or "S" to order grey.

Temperature range: -40 to 105 °C

Short term: Max. 160 °C

Content of delivery:

System supports with two (2) screws for securing the lid (optional).

Mounting accessories not included

Accessories for Nylon Flexible Conduits

SGB Tube Clamps

- Especially suitable for mounting static conduits
- Body: galvanized steel according to DIN 3016
- Coating: elastomer (EPDM) free from halogens
- Smooth connection to PMAFLEX® corrugated conduits
- Good ozone and aging resistance



Temperature range: -50 to 105 °C

Cat. No. Fine Profile, Black	Fits to Conduit Size		Width (mm)	Fixing Screw
	NW	Metric		
SGB-07	7	10	13.0	(1) M4
SGB-09	10	12		
SGB-11	12	16		
SGB-16	17	20	16.0	(1) M5
SGB-21	23	25		
SGB-29	29	32	19.0	(1) M6
SGB-36	36	40		
SGB-48	48	50		

GN Half Shells

- Used for fixing PMA® conduits to beam systems, particularly in traction and machine applications
- High-grade, specially formulated polyamide
- Variable combinations
- Strain relief due to gripping around conduit
- Especially suitable for dynamic applications due to rounded edges
- Variety of support possibilities
- Self extinguishing
- Free from halogens and cadmium
- Excellent impact strength



Temperature range: -40 to 105 °C
Short term: Max. 160 °C

Cat. No. Fine Profile, Black	Cat. No. Coarse Profile, Black	Conduit Size		Outside Diameter (mm)	Width (mm)
		NW	Metric		
BGN-S12T	—	12	16	26.5	34.0
BGN-S17T	BGN-S17G	17	20	32.0	
BGN-S23T	BGN-S23G	23	25	39.5	
BGN-S29T	BGN-S29G	29	32	47.0	
BGN-S36T	—	36	40	55.0	36.5
—	BGN-S36G	36	40	55.0	34.0
BGN-S48T	—	48	50	66.5	36.5
—	BGN-S48G	48	50	66.5	34.0
—	BGN-S70G	70	80	93.5	38.0

Accessories for Nylon Flexible Conduits

GL Tube Clamps

- Used in general machine and installation applications
- High-grade, specially formulated polyamide
- Self extinguishing
- Free from halogens and cadmium



Cat. No. Black	Cat. No. Grey	Conduit Size		Width (mm)	Fixing Screw
		NW	Metric		
BGL-07	SGL-07	07	10	25.0	(1) M4
BGL-10	SGL-10	10	12	27.0	
BGL-12	SGL-12	12	16	31.0	
BGL-17	SGL-17	17	20	39.5	(1) M5
BGL-23	SGL-23	23	25	49.0	
BGL-29	SGL-29	29	32	57.0	(1) M6



Temperature range: -40 to 105 °C

GH Tube Clamps

- Used in general machine and installation applications
- High-grade, specially formulated polyamide
- Self extinguishing
- Free from halogens and cadmium
- Nominal widths: 23–95



Cat. No. Black	Cat. No. Grey	Conduit Size		Width (mm)	Fixing Screw
		NW	Metric		
BGH-23	SGH-23	23	25	58.0	(2) M5
BGH-29	SGH-29	29	32	70.0	
BGH-36	SGH-36	36	40	80.0	(2) M6
BGH-48	SGH-48	48	50	94.0	



Temperature range: -40 to 105 °C