



Family

**Catalog Number:** BKAH-M160  
**Product ID:** 7TAA292400R0001  
**UPC Number:** 78620994657  
**Status:** Active

KAH Connector 45 Degree Elbow, Metric Metal Thread IP69K - Thread M16x1.5, Fits to Conduit NW10, Color Black

### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-45 Degree
Application	For applications with high technical requirements and in most demanding climatic conditions
Size	NW10
Material	Polyamide 6
Insulation Class	IP69K
Color	Black
Connection	M16
Temperature Rating	-50 to +150 Degree Celsius

### European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	12mm
Degree of protection (IP)	Other
Model	45°-elbow
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M16 x 1.5
Thread material	Polyamide
Thread length	11mm
Total length	52.5mm
Total height	44mm
Material	Polyamide
Material sealing	Other
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	N
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-50 - +105°C

### Packaging

Inner Quantity	50
Outer Quantity	250
Outer Dimensions (inches)	15.748x11.811x7.874
Weight Uom	0.03 lbs. Each

### Documents / Support Tools

Video US	Available on Website
----------	----------------------

Video US

Available on Website

**Header**

3D Model

Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)