



Family

Catalog Number: BKAH-M506
Product ID: 7TAA292400R0011
UPC Number: 78620994667
Status: Active

KAH Connector 45 Degree Elbow, Metric Metal Thread IP69K - Thread M50x1.5, Fits to Conduit NW36, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-45 Degree
Application	For applications with high technical requirements and in most demanding climatic conditions
Size	NW36
Material	Polyamide 6
Insulation Class	IP69K
Color	Black
Connection	M50
Temperature Rating	-50 to +150 Degree Celsius

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	40mm
Degree of protection (IP)	Other
Model	45°-elbow
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M50 x 1.5
Thread material	Polyamide
Thread length	19mm
Total length	105.5mm
Total height	95.5mm
Material	Polyamide
Material sealing	Other
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-50 - +105°C

Packaging

Inner Quantity	20
Outer Quantity	20
Outer Dimensions (inches)	15.748x11.811x7.874
Weight Uom	0.06 lbs. Each

Documents / Support Tools

Video US	Available on Website
----------	----------------------

Video US

Available on Website

Header

3D Model

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com