



Representative

Catalog Number: BVEMV-M253-11
Product ID: 7TAA292330R0004
UPC Number: 78620994918
EAN Number: 07630030217128
Status: Active

VEMV Connector, Metric Thread IP68 - Thread M25x1.5, Fits to NW/F.CK/F.CU 23/20/20, Thread Length 11.0mm, Color Black

North American Specifications (UNSPSC)

| | |
|--------------------|--|
| UNSPSC | 39121311 Electrical fittings |
| IGCC | 4441 Electrical fittings |
| Brand Name | PMA |
| Type | Connectors-Straight |
| Application | For Cable Protection Systems In a Wide Range of Applications |
| Size | NW23 |
| Material | Polyamide 6 with Nickel Plated Aluminum Threads |
| Insulation Class | IP68 |
| Color | Black |
| Connection | M25 |
| Temperature Rating | -40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C |

European Specifications (ETIM)

| | |
|--|---|
| ETIM | EC001176 Screw connection for corrugated plastic hose |
| Nominal diameter | 25mm |
| Degree of protection (IP) | IP68 |
| Model | Straight |
| Revolving thread | N |
| Construction type | Internal thread |
| Type of connection | Snap connection |
| Thread type | Metric |
| Thread connection size | M25 x 1.5 |
| Thread material | Other |
| Thread length | 11mm |
| Total length | 90mm |
| Material | Polyamide |
| Material sealing | Other |
| Colour | Black |
| Approved in combination with protective conduit CSA | N |
| Approved in combination with protective conduit UR | N |
| Approved in combination with protective conduit DIN EN 61386-23 | N |
| Approved in combination with protective conduit Lloyd's Register | N |
| Operating temperature | -40 - +105°C |

Packaging

| | |
|---------------------------|---------------------|
| Inner Quantity | 1 |
| Outer Quantity | 40 |
| Outer Dimensions (inches) | 15.748x11.811x7.874 |
| Weight Uom | 0.4 lbs. Each |

Header

3D Model

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com