



Family

**Catalog Number:** BVNV-M253GT  
**Product ID:** 7TAA292150R0278  
**UPC Number:** 78620995236  
**EAN Number:** 07630030231902  
**Status:** Active

VN Straight Connector, Metric Thread for IP66 Static Conduit - Thread M25x1.5, Fits to Conduit Size NW/Metric 23/25, Color Black

### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Fittings for Nylon Flexible Conduits
Application	For Cable Protection Systems In a Wide Range of Applications
Standard	CSA
Size	NW23
Material	Polyamide 6
Insulation Class	IP68GT
Color	Black
Connection	M25
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C

### European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	25mm
Degree of protection (IP)	Other
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M25 x 1.5
Thread material	Polyamide
Thread length	12mm
Total length	52mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

### Packaging

Inner Quantity	30
Outer Quantity	180
Outer Dimensions (inches)	15.748x11.811x7.874
Weight Uom	0.01 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

Video US Available on Website

#### For further technical assistance, please contact us...

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com