

Catalog Number: BVNV-P090GT
Product ID: 7TCA292000R0077
UPC Number: 78621008801
EAN Number: 07630030231513
Status: Active

VN Straight Connector, IP68GT, PG Thread for IP68 Static Conduit - Thread PG 9, Fits to Conduit Size NW/Metric 10/12, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Fittings for Nylon Flexible Conduits
Application	Use In Railway Vehicle and Heavy Machine Construction
Standard	CSA
Size	NW10
Material	Polyamide 6
Insulation Class	IP68GT
Color	Black
Connection	PG09
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	12mm
Degree of protection (IP)	Other
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Other
Thread connection size	PG9
Thread material	Polyamide
Thread length	11mm
Total length	36.5mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	50
Inner Dimensions (inches)	15.74x11.81x7.87
Outer Quantity	700
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.01 lbs. Each

Documents / Support Tools

Video US

Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com