



Family

Catalog Number: BVNZ-M253GT
Product ID: 7TCA292000R0094
UPC Number: 78621005913
EAN Number: 07630030230837
Status: Active

Straight Black Strain Relief Connector, Material - Polyamide 6, Thread Size - M25x1.5, Conduit Size NW - 23, Terminal Range - 13.0 - 18.0, Single Component Version

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5537 Cable insulation hose
Brand Name	PMA
Type	Fittings for Nylon Flexible Conduits
Special Features	IP68GT
Application	For Cable Protection Systems In a Wide Range of Applications. For Separation of Damp and Dry Areas.
Material	High-Grade Specially Formulated Polyamide, Thread Made of Nickel-Plated Brass
Color	Black

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	25mm
Degree of protection (IP)	Other
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M25 x 1.5
Thread material	Polyamide
Thread length	8mm
Total length	81mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	30
Inner Dimensions (inches)	.01x.01x.01
Outer Quantity	120
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.09 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com