



Family

Catalog Number: BVNZ-M406GT
Product ID: 7TCA292000R5939
UPC Number: 78621005915
EAN Number: 07630030297953
Status: Active

Straight Black Strain Relief Connector, Material - Polyamide 6, Thread Size - M40x1.5, Conduit Size NW - 36, Terminal Range - 22.0 - 32.0, Single Component Version

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-Strain Relief
Application	For Use In Machine and Plant Construction
Size	NW36
Material	Polyamide 6
Insulation Class	IP68GT
Color	Black
Connection	M40
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	40mm
Degree of protection (IP)	Other
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M40 x 1.5
Thread material	Polyamide
Thread length	10mm
Total length	108.5mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	20
Inner Dimensions (inches)	.01x.01x.01
Outer Quantity	40
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.09 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com