



Family

Catalog Number: BVNZ-P366S
Product ID: 7TAA292150R0335
UPC Number: 78620995291
EAN Number: 07630030230448
Status: Active

VNZ Straight Connector with Strain Relief, PG Thread for IP68 Static Conduit - Thread PG 36, Fits to Conduit Size NW/Metric 36/40, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-Strain Relief
Application	For Use In Machine and Plant Construction
Size	NW36
Material	Polyamide 6
Insulation Class	IP68
Color	Black
Connection	PG36
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term to 160 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	40mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Other
Thread connection size	PG36
Thread material	Polyamide
Thread length	13mm
Total length	112mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	20
Outer Quantity	40
Outer Dimensions (inches)	15.748x11.811x8.661
Weight Uom	0.2 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com